

## Aquarius T54 D28



- ✓ AMD EPYC 7002
- ✓ PCIe 4-
- ✓ / VDI

	2 x AMD EPYC 7002 , 225W. (cTDP 240 ). 280W.
	4096GB ECC DDR4, 32 L-/R-DIMM 2933/3200
	- - AMD EPYC 700x Aspeed® AST2500
	Riser Card 1: - 1 x PCIe x16 (Gen3 x16 or x8), - 1 x PCIe x8 (Gen3 x0 or x8), - 1 x PCIe x8 (Gen3 x8),
	Riser Card 2: - 1 x PCIe x16 (Gen3 x16 or x8), - 1 x PCIe x8 (Gen3 x0 or x8), - 1 x PCIe x8 (Gen3 x8),
	Riser Card 3: - 1 x PCIe x8 (Gen3 x0 or x8), - 1 x PCIe x16 (Gen3 x16 or x8),
	2 x OCP mezzanine - PCIe Gen3 x16 - Type1, P1, P2, P3, P4, K2, K3
	Aspeed® AST2500, 1920x1200@ 60Hz 32bpp
	1 2 x 3.5" / 2.5" SATA/SAS HDD/SSD

	1x		
	1x	HDD	
	2x	LAN	
	1x	!	
	2 x 1GbE LAN	(1 x Intel® I350-AM2)	
	1 x 10/100/1000 LAN		
	2 x 1600/2000W	80 PLUS Platinum	(1+1)
	4 x 80x80x38mm		
	Aspeed® AST2500:		
	-		
	- JAVA SOL		
	- HTML5 KVM		
	- (Voltage, RPM, Temperature, CPU Status )		
	-		
	- FRU		
	- SEL / Circular Storage Policy		
	-		
	-		
	- Firewall		
	-		
	-		
	- LDAP / AD / RADIUS		
	-		
	- BIOS/BMC/CPLD		
	-		
	-		
	-		
	- SSL / SMTP		
( x x ),	268	588	982
,	22		
/	6 x SlimSAS		
	1x M.2		
	1x USB 3.0		
	1x TPM		

Windows Server 2016  
Windows Server 2019  
Red Hat Enterprise Linux 7.6 (x64)  
Red Hat Enterprise Linux 8.0 (x64)  
SUSE Linux Enterprise Server 12 SP4 (x64)  
SUSE Linux Enterprise Server 15 SP1 (x64)  
Ubuntu 16.04.6 LTS (x64)  
Ubuntu 18.04.3 LTS (x64)  
Ubuntu 20.04 LTS (x64)  
VMware ESXi 6.5 EP15  
VMware ESXi 6.7 Update3  
VMware ESXi 7.0