






A separation module visually divides a fieldbus node into sections.

The 750-616 Separation Module has no power jumper contacts. A separation module with printing on its face has got the item no. 750-616/030-000.

Note:

Operation of the adjacent I/O modules requires a supply module.

The 750-621 Separation Module has power jumper contacts that can supply the power to adjacent bus modules.

Description	Item No.	Pack. Unit	Technical Data	
Separation Module	750-616	1	Width	12 mm
Separation Module/ 24V DC/ 230V AC	750-616/030-000	1	Weight	38.9 g
Separation Module with Contacts	750-621	1	EMC immunity of interference	acc. to EN 61000-6-2, marine applications
			EMC emission of interference	acc. to EN 61000-6-4, marine applications
Accessories	Item No.	Pack. Unit		
Miniature WSB Quick marking system				
 plain	248-501	5		
with marking	see Section 11			
Approvals				
Conformity marking	CE			
Korea Certification				
Marine applications (versions upon request) ¹⁾	ABS, BV, DNV, GL, KR, LR, NKK, PRS, RINA			
 UL 508				
 ANSI/ISA 12.12.01	Class I, Div. 2, Grp. ABCD, T4			
 TÜV 07 ATEX 554086 X	I M2 Ex d I Mb, II 3 G Ex nA IIC T4 Gc, II 3 D Ex tc IIIC T135°C Dc			
IECEX TUN 09.0001 X	Ex d I Mb, Ex nA IIC T4 Gc, Ex tc IIIC T135°C Dc			
¹⁾ Does not apply to 750-621				